



COD	Ø	mm	Str	Box
PA2003	47	180	STL8C ø8 roller sleeve ricambio estraibile t8	60
		200		
	55	230	STLMA8C with ø8 stick frame con manico t8	40
		250		
	47	180	STL8C ø8 roller sleeve ricambio estraibile t8	40
		200		
	55	230	STLMA8C with ø8 stick frame con manico t8	36
		250		

6.6 RHODIA POLYAMIDE 20

Tucked



UNDERCOAT

excellent paint exchange
high mq performance
high-hiding power thick coverage

Material = **polyamide**
Pile = **medium 20 mm**

Twisted yarn medium pile polyamide paint roller. High-grade hard-wearing and long-lasting fabric, ideal for fillers and high-coverage satin latex paints on internal or external cement mortar and fiber-cement supports. Tucked paint roller to enhance the application on corners.

Intended use

Latex paints and primers for base-coverage, matt and satin paints on coarse surface, protective and barrier coating with quartz, silicate and siloxanic varnishes.

Paints

WATER-BASED PAINT
INSULATOR
ACRYLIC
SILICATE
SILOXANE
QUARTZ PAINT

Surfaces

EXTERNAL WALL
INTERNAL WALL
PLASTERING MORTAR
LIME-CEMENT
CONCRETE
PREFAB

NYLON 6.6 RHODIA 20

Rimboccato



FONDI

eccellente carico e scarico del colore
alta resa per mq
rullata coprente ad alto spessore

Materiale = **nylon**
Pelo = **medio 20 mm**

Rullo in poliammide a pelo medio arruvidito sulle punte. Filato di alta qualità resistente ad usura e abrasione, ideale per fondi riempitivi e idropitture opache ad alta copertura su strutture cementizie e in fibrocemento all'interno o all'esterno. Rullo rimboccato per ottimizzare l'applicazione negli angoli.

Destinazione d'uso

Idropitture e primer per coperture base, pitture opache e satinare su fondi grezzi, rivestimenti barriera e protettivi con pitture al quarzo, silicati e silossanici.

Vernici

IDROPITTURE
ISOLANTI
ACRILICI
SILICATI
SILOSSANICI
PITTURE AL QUARZO

Superfici

MURI ESTERNI
MURI INTERNI
CALCE-CEMENTO
CALCESTRUZZO
PREFABBRICATO
INTONACO A MALTA