



| COD | Ø | mm | Str | Box |
|--------|----|-----|---|-----|
| PA2004 | 55 | 180 | STL8C ø8 roller sleeve ricambio estraibile t8 | 40 |
| | | 200 | | |
| | | 230 | | |
| | | 250 | STLMA8C with ø8 stick frame con manico t8 | 36 |

6.6 RHODIA POLYAMIDE 20



Material = **polyamide**
Pile = **medium 20 mm**

excellent paint exchange
high mq performance
high-hiding power thick coverage

Twisted yarn medium pile polyamide paint roller. High-grade hard-wearing and long-lasting fabric, ideal for fillers and high-coverage satin latex paints on internal or external cement mortar and fiber-cement supports. Great performance even on coarse surfaces.

Intended use

Latex paints and primers for base-coverage, matt and satin paints on coarse surface, protective and barrier coating with quartz, silicate and siloxanic varnishes.

Paints
PIGMENT PRIMER
INSULATOR
ACRYLIC
SILICATE
SILOXANE
QUARTZ PAINT

Surfaces
EXTERNAL WALL
INTERNAL WALL
LIME-CEMENT
PLASTERING MORTAR
CONCRETE
STUCCO

NYLON 6.6 RHODIA 20



Materiale = **nylon**
Pelo = **medio 20 mm**

eccellente carico e scarico del colore
alta resa per mq
rullata coprente ad alto spessore

Rullo in poliammide a pelo medio arruvidito sulle punte. Filato di alta qualità resistente ad usura e abrasione, ideale per fondi riempitivi e idropitture opache ad alta copertura su strutture cementizie e in fibrocemento all'interno o all'esterno. Ottime performance anche sui fondi più grezzi.

Destinazione d'uso

Idropitture e primer per coperture base, pitture opache e satinate su fondi grezzi, rivestimenti barriera e protettivi con pitture al quarzo, silicati e silossanici.

Vernici
PRIMER PIGMENTATI
ISOLANTI
ACRILICI
SILICATI
SILOSSANICI
PITTURE AL QUARZO

Superfici
MURI ESTERNI
MURI INTERNI
CALCE-CEMENTO
CALCESTRUZZO
INTONACO A MALTA
STUCCO